

# DUAL DASH CAMERA C1

Dual Channel 4G LTE Dash Camera designed for consumer vehicles, taxis, and fleet operations, delivering reliable front and cabin/rear full-HD recording. Enables real-time video streaming, cloud connectivity, GPS tracking, and smart event-based uploads for enhanced visibility and remote fleet management. Equipped with AI-powered ADAS features, driver monitoring, incident detection, and proactive safety alerts to improve road safety, compliance, and operational efficiency.



## FEATURES



Event Based  
Video Locking



G-sensor Based  
Incident Detection



In-Cabin  
Audio Alerts



Forward  
Collision Warning



Lane  
Departure Warning



Camera Blocker  
& Tamper Detection

## Technical Specification

General	Product Type	Dual Channel LTE Dash Camera	Connectivity	Cellular	4G LTE	
	Use Case	Consumer Vehicles / Taxi / Fleet		Wi-Fi	2.4 GHz / 5 GHz	
	Operating System	Android 13		Wi-Fi Standard	IEEE 802.11 a/b/g/n/ac	
Processor & Memory	Processor	Qualcomm SC6688S Smart Module	Sensors	Bluetooth	BLE 5.0	
	CPU	Kryo Gold Quad-Core @ 2.0 GHz + Kryo Silver Quad-Core @ 1.8 GHz		GNSS	GPS / GLONASS	
	RAM	4 GB LPDDR4X		Display	G-Sensor	Supported
	Internal Storage	64 GB eMMC			Screen Type	LCD
Front Camera	Sensor	Sony IMX335	Power	Touchscreen	Supported	
	Resolution	1080P		Power Input	5V DC	
	Effective Pixels	5 MP	Security	Interface	USB Type-C	
	Frame Rate	Up to 30fps		Battery	800mAh	
	Sensor	Sony IMX335		Secure Boot	Supported	
Cabin / Rear Camera	Resolution	1080P	Software & Platform	Firmware Encryption	Supported	
	Frame Rate	Up to 30fps		Data Encryption	Supported	
Video & Imaging	Video Encoding	H.264	Interfaces	Mobile App	Android App Support	
	Video Format	MP4		OTA Updates	Supported	
	HDR	Supported	Indicators	USB	Type-C	
	Night Vision	Supported		MicroSD Slot	Supported	
Audio	Microphone	Built-in	SIM Slot	Supported		
	Speaker	Built-in	Reset Button	Supported		
Storage	Storage Type	MicroSD Card	Recording ON/OFF	LED Indicator	Supported (4G, GPS, WIFI, Recording ON/OFF)	
	Max Capacity	Up to 512 GB				
	Storage Encryption	Supported				
Environmental	Cellular	4G LTE				
	Wi-Fi	2.4 GHz / 5 GHz				
Environmental	Operating Temp.	-20°C to +70°C				
	Storage Temp.	-40°C to +90°C				

Explore our full product portfolio at [www.rapidise.co](http://www.rapidise.co)

For partnerships and enterprise deployments, contact: [sales@rapidise.co](mailto:sales@rapidise.co)